



Features

Dual Function body can be used as lockshield or wheelhead

Body can be mounted vertically or horizontally



Bidirectional Flow
(Either direction through body)



Can be used in conjunction with Tower radiator thermostats

TRV2



15mm compression fittings



Supplied with BSP Tailpiece



Supplied with witches hat for lockshield applications



Robust high quality chrome finish

PRODUCT DATA SHEET

MANUAL RADIATOR VALVE LOCKSHIELD

PRODUCT CODE: **LS1**



Application

The LS1 manual radiator valve can be used as a lockshield or wheelhead.

Suitable for fully pumped systems up to 10 bar static pressure.

Components




Specification

Max Flow Temp	: 90°C (194°F)
Max working Pressure	: 10bar (150psi)
Radiator connection	: 1/2" BSP
Pipework connections	: 15mm

TFC GROUP LLP

MANUAL RADIATOR VALVE / LOCKSHIELD



Cert No: RS 30178
QR057

TFC GROUP LLP, TOWER HOUSE, VALE RISE, TONBRIDGE, KENT TN9 1TB

Tel: 01732 351680 Fax: 01732 354445 www.tfc-group.co.uk

Prepared for TFC Group LLP By: M. Edmonston

Issue 1: July 2018

Page 1 of 1