

## **PRODUCT DATA**

## **OP-TOUCHRF**

RADIO FREQUENCY
TOUCHSCREEN THERMOSTAT

SIMPLE OPERATION

**BLUE BACKLIT DISPLAY** 

**LARGE 40mm DIGITS** 

**CLEAR DEMAND INDICATOR** 

WALL-MOUNTED RECEIVER



OP-TOUCHRF IS A CAPACITIVE TOUCH-SCREEN RADIO FREQUENCY THERMOSTAT. SUIT-ABLE FOR WALL MOUNTING, OR FOR USE WITH TABLE-TOP STAND. BATTERY POWERED TRANSMITTER (Tx). WALL-MOUNTED RECEIVER (Rx) WITH VOLT-FREE CONNECTION. ADJUSTABLE IN THE RANGE 5—35 DEGREES. TOUCH THE RIGHT-HAND SIDE OF THE SCREEN TO INCREASE THE SET TEMPERATURE, OR THE LEFT-HAND SIDE OF THE SCREEN TO REDUCE THE SET TEMPERATURE. IF THE MEASURED TEMPERATURE IS BELOW THE SET TEMPERATURE, THE OP-TOUCH WILL SEND A SIGNAL VIA THE RECEIVER, TO SWITCH THE HEATING ON.

TRANSMITTER DIMENSIONS mm 83.5 x 111 x 33.5

RECEIVER DIMENSIONS mm 86 X 90 X 25

RECEIVER CONNECTIONS 4 X WIRE-PROTECT SCREW TERMINALS

RECEIVER SWITCHING CAPACITY 2 AMPERES

POWER SUPPLY Tx: 2 x AA ALKALINE Rx: 230V 50Hz


TEMPERATURE RANGE  $5-35^{\circ}$ C
TEMPERATURE REGULATION +/-  $1^{\circ}$ C

ADJUSTABLE SETTINGS MEASURED TEMPERATURE & DIFFERENTIAL

DEMAND INDICATOR HEAT SYMBOL



RECEIVER WIRING SCHEMATIC



## **SPTIMUM**

